

LATIGUILLOS Y MANGUERAS TERMOPLÁSTICAS DE ULTRA ALTA PRESIÓN

- Interior: POM o PA 11/12
- Refuerzo: Trenzados de acero de alta resistencia
- Exterior: PA 11/12
- Temperatura de trabajo: -30° C a +60° C

TIPO	Ø		Ø Exterior Casquillo	Presión Trabajo	Presión rotura mínima	Radio Curvatura mínimo	Peso
	Interior	Exterior					
	mm	mm					

TIPO 2

32	3,0	7,0	9,1	1.100	2.750	60	0,072
42	4,0	8,0	10,0	1.200	3.000	75	0,110
52	5,0	9,4	12,0	1.000	2.500	95	0,125
62	6,3	11,5	13,5	1.100	2.750	110	0,200
82	8,1	13,3	16,1	900	2.250	120	0,250

TIPO 4

34	3,0	8,0	9,8	2.000	5.000	100	0,12
44	4,0	9,9	12,8	2.200	4.500	100	0,14
54	5,0	11,5	15,3	1.800	4.500	130	0,28
64	6,3	12,5	17,0	1.640	4.100	155	0,33
84	8,0	15,1	21,0	1.500	3.800	175	0,44
104	9,7	19,4	26,0	1.400	3.500	190	0,73
134	12,8	22,5	30,0	1.300	3.250	200	0,94
204	19,6	30,0	38,0	1.000	2.500	250	1,39

TIPO 4H

134H	12,8	25,0	30,0	1.400	3.500	110	1,190
------	------	------	------	-------	-------	-----	-------

TIPO 6

46	4,0	12,0	15,6	2.800	7.000	140	0,29
56	4,8	13,2	18,3	2.800	7.000	200	0,47
86	8,0	16,9	22,0	2.100	5.250	225	0,68
136	12,8	24,5	34,0	1.800	4.500	450	1,36
206	19,6	40,0	40,6	1.400	3.500	350	2,10

TIPO 6H

56H	4,8	13,2	18,6	2.800	7.000	200	0,470
86H	7,8	17,2	22,8	2.500	6.250	200	0,830
136H	12,7	27,0	31,9	2.000	5.000	300	1,850

TIPO 8

58	4,6	15,0	18,8	4.000	8.000	200	0,660
88	7,8	19,5	24,0	3.000	7.000	250	1,100
128	12,7	29,8	34,2	2.500	6.250	350	2,500

TIPO 8H

88H	7,8	19,6	24,0	3.200	8.000	280	1,100
138H	13,0	29,9	34,2	3.000	6.250	350	2,500

